Moralt Door Kit

A PASSIVE HOUSE COMPLIANT DOOR KIT WITH ACCESSORIES.

NEW: PAS 24 certified

CE-MARKED - EN14351-1:2006, EXTERNAL WINDOWS & DOORS




Passivhaus – Passive House

A Passive House is a building in which a comfortable interior climate can be maintained without active heating and cooling systems. The house heats and cools itself, hence the term "passive".

Typically a Passive House operates on the following basis:

- passive external heat gains from the sun as well as internal gains from appliances and the building's occupants
- significantly notable levels of airtightness and insulation with minimal thermal bridges
- a high level of internal air quality provided by a mechanical ventilation system that recovers heat efficiently

The inclusion of high level thermally insulated windows and doors is critical in achieving these criteria. This Passive House Institute certified component is your opportunity to participate in this exciting new concept.



Passage of temperature through the door element













- The Moralt Passive House door blank is a certified Passive House component from the Passive House Institute in Darmstadt, Germany.
- The Passive House door blank has a U Value of 0,54 W/m^2K ; the Passive House door, as supplied in kit form by James Latham has a U Value of \leq 0,80W/m²K (with and without glazing).
- The Moralt Passive House door blank is CE certified (EN14351-1:2006 External Doors and Windows) and attains the best results in all mandatory aspects of this standard. Eg, wind-load resistance EN 12210, security classification WK2 (door blank resistance classification 3) ENV 1627, airtightness classification EN 12207.





MDF faces

Solid PU thermal core



Flat steel





stabilizer



Robust construction





FD 30



Acoustic insulation dB 43 on request

Fire-rating FD 30/EI 30 on request


DOOR BLANK



Moralt Passive House Door Kit

MORALT FERRO PASSIV HOUSE DOOR KIT		
Maximum manufacturing sizes		
Frame size	upto 1.200 x 2.520 mm	
Blank Size	upto 1.150 x 2.470 mm	
Door blank thickness 98 mm		
Facings 5 mm thick		
MDF*	exterior grade	
Meranti	5 ply long grain Fineline veneer	
Okoume*	5 ply long grain sliced veneer	
Oak	5 ply long grain sliced veneer	
Pine	5 ply long grain Fineline veneer	
Stiles & Rails and door frames		
engineered solid timber		
Meranti*	when Okoume or Meranti facings	
Oak*	when Oak facings	
Pine*	when Pine or MDF facings	

* available with ESC certification




WHAT IS INCLUDED IN THE DOOR KIT?

MORALT STANDARD COMPONENT PACKAGE	
Door	Moralt FERRO Passiv
Frame	3 Pieces
Hinges	Simonswerk BAKA 2D 20 FD
Lock	3 Point Lock
Threshold	GU Systemhaustürschwelle
Seal	Deventer DS 155a anthrazit
Packaging	Boxed with foam corners



CE











Further information and samples can be obtained from the James Latham marketing department. Phone: 0116-257-3415 Email: marketing@lathams.co.uk or click on www.lathamtimber.co.uk